

RabbitMQ

- [Get started](#)

Get started

Neue User anlegen

Quelle: <https://stackoverflow.com/questions/23020908/how-to-access-rabbitmq-publicly>

First of all connect to your rabbitmq server machine using ssh client so as to be able to run `rabbitmqctl` (like puTTY) & get into the sbin directory of rabbit installation

1. you need to create a user for any vhost on that system (here I use default vhost `"/`)

```
$ rabbitmqctl add_user yourName yourPass
```

2. Set the permissions for that user for default vhost

```
$ rabbitmqctl set_permissions -p / yourName ".*" ".*" ".*"
```

3. Set the administrator tag for this user (to enable him access the management pluggin)

```
$ rabbitmqctl set_user_tags yourName administrator
```

... and you are ready to login to your rabbitmq management gui using `yourName` and `yourPass` from any browser by pointing it to `http://"*****":15672` where `*****` is your server IP

Plugin aktivieren

Management (WebUI) Plugin aktivieren: `/usr/lib/rabbitmq/lib/rabbitmq_server-0.0.0/sbin/rabbitmq-plugins enable rabbitmq_management`

Wenn ich nur `rabbitmq-plugins enable rabbitmq_management` aufrufe dann meckert er rum, dass er das Plugin nicht findet. Da scheint noch was in den configs zu fehlen.